

MOBILE "COMPACT SERIES" STACKERS

"SHOPLIFTER"

MODEL: SSL40

The Mobile "Shoplifter" Stacker is designed for applications in tight, compact areas. This manual push, power lift unit allows the operator to increase productivity while reducing fatigue and injury caused by lifting, stretching and bending.

Featuring a fork over straddle design, the SSL40 is ideal for lifting skids and other bottomless containers. Machine shops and warehouses utilize this unit for transporting parts and small products. Specifically, Screw Machine Shops use it for handling baskets, while Stamping Plants find it ideal for handling pans.

Combining ergonomics and efficiency, the SSL40 is easy to operate, requires a minimum of maintenance and is extremely durable. Mobile is also able to custom design to suit specific applications - call for details.



FEATURES:

Frame: Rugged heavy duty frame constructed of formed and welded steel for extra strength.

Mast: Fabricated with channel steel for greater strength and dependability.

Lifting Chains: Unique dual lifting chains are roller style, heavy duty steel exceeding a 6:1 safety factor.

Hydraulic System: Durable cylinder features a chrome plated ram and a relief valve for overload protection.

Forks: Heavy duty steel 4" wide X 18" long fixed forks.

Battery: Features a heavy duty 12 volt, 125 amps/hour industrial strength battery.

Charger: The built-in battery charger is a 10 amp Selenium rectifier with transformer, circuit breaker and overload protection - plugs into any 110 volt outlet.

Steering: Features 5" phenolic rear casters for easy maneuverability.

Wheels: Features 3" phenolic wheels with roller bearings located in the straddle legs.

Brake: Features a hand controlled floor lock brake that secures the unit in place.

Options: AC Power
Remote Control

SPECIFICATIONS:

Load Capacity:	500 lbs.
Load Center:	9"
Raised Fork Height:	40"
Lowered Fork Height:	3.25"
Fork Width:	4"
Fork Length:	18"
Overall Mast Height:	48"
Overall Width:	25"
Overall Length:	35"
Weight:	500 lbs.
Casters:	5" Phenolic
Front Wheels:	3" Phenolic
Battery:	12V/125A heavy duty
Charger:	12V/10A w/overload protect